AMENDMENT

In the Claims

Please amend claims 1. 19, and 20 as follows.

1. (Currently Amended)   A method for achieving an end-to-end data flow rate supported by a communications network having a source and a destinatior interconnected by communication links, the method comprising the steps c :

initiating a data flow at the source over the links, the data flow comp ising a plurality of packet pairs;

measuring an amount of data received at the destination over a predetermined time interval;

measuring a packet gap for each packet pair received at the destina ion over the predetermined time interval; and

determining, in response to the measured data and packet gap, a supportable data flow rate in the network so that the data flow initiated by tl e source can flow through the network without loss of data and without subst ntial buffering.

2. (Original)   The method of Claim 1 wherein the end-to-end data flow rate extends from the source to the destination of the network, the data flow rate being at or below a bottleneck rate of the network.

3. (Original)   The method of Claim 1 wherein the step of determining furthe comprises the step of providing feedback to the source.

Docket No.: 42P19777   2   Exam er: Sol
Ser. No.: 10/038,329   Art Ur t: 2662

PAGE 7/13 * RCVD AT 10/24/2005 7:10:23 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/25 * DNIS:2738300 * CSID:2062928606 * DURATION (mm-ss):02-36

4. (Original) The method of Claim 3 wherein the step of providing feedback further comprises the step of communicating the supportable data flow rate to the source in the form of end-to-end credits extended to the source.

5. (Original) The method of Claim 4 wherein the end-to-end credits enable transmission of a specific amount of data by the source over the predetermined time interval.

6. (Original) The method of Claim 5 further comprising the steps of:

calculating an expected packet gap based on previously extended credits; and

determining if the measured packet gap is equal to or greater than the expected gap, or less than the expected gap.

7. (Original) The method of Claim 6 wherein the steps of measuring and calculating allows the destination to inform the source whether to decrease or increase the amount of data flow during a next time interval.

8. (Original) The method of Claim 7 further comprising the steps of:

if the measured data is less than expected, decreasing the credits extended to the source for the next interval;

if the measured data is equal to the extended credits, using the measured packet gap to determine whether to increase the credits; and

if the measured gap is less than expected, extending more credits from the destination to the source to thereby probe the network capacity.

9. (Original) The method of Claim 8 further comprising the steps of:

Docket No.: 42P19777   3   Examiner: Sol
Ser. No.: 10/038,329   Art Unit: 2662

PAGE 8/13 * RCVD AT 10/24/2005 7:10:23 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/25 * DNIS:2738300 * CSID:2062928606 * DURATION (mm-ss):02-36

providing a credit-based flow control mechanism; and

pacing out the data over the time interval in accordance with the credit-based flow control mechanism.

10. (Original) The method of Claim 9 wherein the step of providing the credit-based flow control mechanism comprises the step of implementing the credit-based flow control mechanism as a leaky bucket.

11. (Original) The method of Claim 9 wherein the paced out data is sent by the source in groups of two packets, back-to-back.

12. (Original) The method of Claim 1 wherein the step of measuring the packet gap further comprises the step of averaging a plurality of packet gap measurements performed at the destination during the time interval.

13. (Original) A system adapted to achieve an end-to-end data flow rate supported by a communications network having a source and a destination interconnected by communication links, the system comprising:

a credit-based flow control mechanism configured to regulate packet pairs of a data flow over a predetermined time interval; and

congestion management logic configured to measure an amout of data received at the destination that has traversed the network over the time interval and to measure a packet gap for each received packet pair to determine if capacity of the network has increased, the congestion management logic further calculating an expected packet gap and determining if the measured packet gap is equal to or greater than the expected gap, or less than the expected gap

Docket No.: 42P19777   4   Exam ier: Sol
Ser. No.: 10/038,329   Art U t: 2662

PAGE 9/13 * RCVD AT 10/24/2005 7:10:23 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/25 * DNIS:2738300 * CSID:2062928606 * DURATION (mm-ss):02-36

wherein a combination of the calculation and measurements allows the destination to inform the source whether to decrease or increase the amount of data sent during a next time interval.

14. (Original) The system of Claim 13 wherein the congestion management logic comprises:

a measure circuit configured to measure the amount of data received form the source and the packet gap over the predetermined time interval; and

a flow control circuit coupled to the measure circuit, the flow control circuit configured to determine credits extended to the source for a subsequent data flow in response to the amount of measured data and the measured gap.

15. (Original) The system of Claim 14 wherein the flow control circuit is further configured to generate a feedback message indicating the credits extended to the source for its subsequent data flow.

16. (Original) The system of Claim 15 wherein the measure circuit is further configured to measure the packet gap between reception of an end of a first packet of the packet pair to reception of a beginning of second packet of the packet pair to determine whether adjustment of the end-to-end data flow rate is necessary.

17. (Original) The system of Claim 16 wherein the measure circuit is further configured to average a plurality of the packet gap measurements over the predetermined time interval.

Docket No.: 42P19777   5   Exam er: Sol
Ser. No.: 10/038,329   Art U t: 2662

PAGE 10/13 * RCVD AT 10/24/2005 7:10:23 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/25 * DNIS:2738300 * CSID:2062928606 * DURATION (mm-ss):02-36

18. (Original) The system of Claim 17 wherein the data sent under credit-based flow control is paced by a leaky bucket mechanism.

19. (Currently amended)   Apparatus for achieving an end-to-end data flow rate supported by a communications network having a source and a destination interconnected by communication links, the apparatus comprising:

     means for initiating a data flow at the source over the links, the data flow comprising a plurality of packet pairs paced out over a predetermined time interval;

     means for measuring an amount of data received at the destination over the predetermined time interval;

     means for measuring a packet gap for the packet pairs at the destination over the predetermined time interval;

     means for calculating an expected packet gap based on previously extended credits;

     means for determining if the measured packet gap is equal to or greater than the expected gap, or less than the expected gap; and

     means for determining, in response to the means for measuring and calculating, a supportable data flow rate in the network so that the data flow initiated by the source can flow through the network without loss of data and without substantial buffering.

20. (Currently amended)   A computer readable medium containing executable program instructions for achieving an end-to-end data flow rate supported by a communications network having a source and a destination interconnected by communication links, the executable program instructions comprising program instructions for:

Docket No.: 42P19777   6   Exam ier: Sol
Ser. No.: 10/038,329   Art Ui t: 2662

PAGE 11/13 * RCVD AT 10/24/2005 7:10:23 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/25 * DNIS:2738300 * CSID:2062928606 * DURATION (mm-ss):02-36

initiating a data flow at the source over the links, the data flow comprising a plurality of packet pairs paced out over a predetermined time interval;

measuring an amount of data received at the destination over the predetermined time interval;

measuring a packet gap for the packet pairs at the destination over he predetermined time interval;

calculating an expected packet gap based on previously extended c edits;

determining if the measured packet gap is equal to or greater than tl e expected gap, or less than the expected gap; and

determining a supportable data flow rate in the network so that the c ata flow initiated by the source can flow through the network without loss of data and without substantial buffering.

Docket No.: 42P19777   7   Exam ier: Sol
Ser. No.: 10/038,329   Art Ui t: 2662

PAGE 12/13 * RCVD AT 10/24/2005 7:10:23 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/25 * DNIS:2738300 * CSID:2062928606 * DURATION (mm-ss):02-36